

DIRECTIONS:

Truck Washing: Dilute 32:1 with water. Spray product onto surface with low pressure, then rinse thoroughly with high pressure water. For brushless cleaning, at least 500 psi pressure is required for rinsing. Hold nozzle 12 inches from vehicle surface while rinsing.

2-Step Cleaning: HD Truck Wash may be used as Step 2 in a 2-Step Cleaning process in combination with an acid product. Dilutions will vary between 32:1 and 64:1.

HD TRUCK WASH

Non-Phosphate Truck Wash & Bug Remover

DANGER

KEEP OUT OF REACH OF CHILDREN
Net Contents: 55 gal (208.20 L)

HD Truck Wash is a premium truck wash that removes diesel exhaust deposits, road film and bug residue from painted vehicle surfaces without time consuming brushing. It rinses easily and leaves no soap film residue when diluted properly.

DANGER

Causes severe skin burns and eye damage. Wash hands thoroughly after handling. Wear protective gloves. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Dispose of contents/container in accordance with federal, state and local regulations.

INGREDIENTS (CAS#): Water (7732-18-5), Sodium Hydroxide (1310-73-2), Tetrasodium EDTA (64-02-8), 2-Butoxyethanol (111-76-2), Surfactants.



0890-055



Detco Industries, Inc.
Conway, AR
1-800-282-2133
www.detco.com